



TECHNICAL DATA SHEET

ENCAP GLOSS 125 MICRON

Product Description

Bi-axially Oriented Polyester Film, Polyethylene Terephthalate (PET) - Encapsulation thermal film with **GLOSS** finish - Both side Corona treated - Low melt adhesive coating inside - Excellent optical properties and good resistance to scuff, scratch & tear

Typical Properties				
Property		Unit	Test Method	Value
Thickness		(μm)		125
Yield		m ² /kg .	ASTM D 4321	6.89
Unit Weight		g/m ²		145
Tensile Strength	MD	kg/mm ²	ASTM D882	12.1
	TD	kg/mm ²	ASTM D882	11.6
Elongation at Break	MD	%	ASTM D882	137
	TD	%	ASTM D882	137
Gloss Value	B			92.1
Haze		%	ASTM D1003	86.9
Wetting Tension	A + B	Dynes/cm	ASTM D 2578	42
Application Temperature	A	°C		100-130
A: Adhesive Side B: Gloss Side				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk