



TECHNICAL DATA SHEET

ENCAP MATT 75 MICRON

Product Description

Bi-axially Oriented Polyester Film, Polyethylene Terephthalate (PET) - Encapsulation thermal film with **MATT** finish - Both side Corona treated - Low melt adhesive coating inside - Excellent optical properties and good resistance to scuff, scratch & tear

Typical Properties				
Property		Unit	Test Method	Value
Thickness		(μm)		75
Yield		m^2/kg	ASTM D 4321	12.19
Unit Weight		g/m^2		82
Tensile Strength	MD	kg/mm^2	ASTM D882	8.5
	TD	kg/mm^2	ASTM D882	10.4
Elongation at Break	MD	%	ASTM D882	124
	TD	%	ASTM D882	111
Gloss Value	B	%		92.1
Haze		%	ASTM D1003	87.6
Wetting Tension	A + B	Dynes/cm	ASTM D 2578	42
Application Temperature	A	$^{\circ}\text{C}$		100-130
A: Adhesive Side B: Gloss Side				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
T: 01844 208308, F: 01844 208608
Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk