



## TECHNICAL DATA SHEET

### THERMAL GSP GLOSS 30 MICRON

#### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Thermal lamination film with **HIGH GLOSS** finish - Low melt adhesive coating inside - Excellent optical properties and good resistance to elongation and tear - **GLUEABLE/STAMPABLE/PRINTABLE**

Typical Properties					
Graphic Image Films Thermal GSP Gloss	Property		Unit	Test Method	Value
	Thickness		( µm )	ASTM E 252	30
	Yield		m <sup>2</sup> /kg .	Internal Method	35,5
	Unit Weight		g/m <sup>2</sup>		27,3
	Gloss	B	%	ASTM D 2457	55
	Wetting Tension	B	Dynes/cm	ASTM D 2578	44
	C.O.F Film/Film (Static)	B/B		ASTM D 1894	0,45
	Application Temperature	A	°C		95-115
	A: Adhesive Side B: Gloss Side				

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
 T: 01844 208308, F: 01844 208608  
 Email: [info.gif@graphicimagefilms.co.uk](mailto:info.gif@graphicimagefilms.co.uk)  
[www.graphicimagefilms.co.uk](http://www.graphicimagefilms.co.uk)