



TECHNICAL DATA SHEET

THERMAL GSP MATT 25 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Thermal lamination film with **MATT** finish - Low melt adhesive coating inside - **GLUEABLE/STAMPABLE/PRINTABLE**

| Typical Properties | | | | |
|--------------------------|-----------|--------------------|-----------------|--------|
| Property | | Unit | Test Method | Value |
| | Thickness | | (µm) | |
| Yield | | m ² /kg | Internal Method | 45,5 |
| Gloss | B | % | ASTM D 2457 45° | 7 |
| Wetting Tension | B | Dynes/cm | ASTM D 2578 | 46 |
| C.O.F Film/Film (Static) | B/B | | ASTM D 1894 | 0,4 |
| Application Temperature | A | °C | Internal Method | 95-115 |

A: Adhesive Side B: Matt Side

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk