



TECHNICAL DATA SHEET

THERMAL SOFT TOUCH PRESTIGE 30 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) -Thermal lamination film with **SOFT TOUCH** finish - Exclusive Peach skin texture and superior bonding strength - Enhances original colours of your print - Outstanding surface adhesion of all types of coatings, inks & foils - Improved machinability compared with previous versions - Low melt adhesive inside

Typical Properties					
Graphic Image Films Thermal Soft Touch Prestige	Property		Unit	Test Method	Value
	Thickness		(µm)	ASTM E 252	30
	Yield		m ² /kg .	ASTM D 4321	37,5
			ln ² /Lb		26,333
	Unit Weight		g/m ²	Derprosa - 009	27,0
	Gloss	B	%	ASTM D 2457 45°	6
	Wetting Tension	B	Dynes/cm	ASTM D 2578	≥ 46
	C.O.F Film/Film	B/B			0.75
	Application Temperature	A	°C		105 - 120
			°F		220-250
	Lamination Strength	A	N25,4/mm		≥ 7,5
			Lb/ln		≥ 1,68
	A: Adhesive Side B: Soft Touch Side				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk