



TECHNICAL DATA SHEET

DIGI-STICK ANTI-SCRATCH MATT 30 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Thermal lamination film with **MATT ANTI-SCRATCH** finish - Premium anti-scratch coating designed to combat against all types of scratches - UV Ink, Spot UV & Stamping Foil compatible - Specially formulated high bond low melt adhesive for Digital inks

Typical Properties				
Property		Unit	Test Method	Value
Thickness		(µm)	Internal Method	30
Yield		m ² /kg .	ASTM D 4321	37,04
		ln ² /Lb		26041
Gloss	B	%	ASTM D 2457 45°	6
Wetting Tension	B	Dynes/cm	ASTM D 2578	>42
C.O.F Film/Film	B/B		ASTM D 1894	0.35
Application Temperature	A	°C		100-115
		°F		230-250
Lamination Strength	A	N25/mm	ASTM D 882	≥8
		Lb/ln		≥1,80
A: Adhesive Side B: Matt Anti-scratch Side				

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info@gifsupplies.co.uk
www.gifsupplies.co.uk