



TECHNICAL DATA SHEET

ENCAP TRUE MATT 125 MICRON

Product Description

Bi-axially Oriented Polyester Film, Polyethylene Terephthalate (PET) - Encapsulation thermal film with **TRUE MATT** finish - Low melt adhesive coating inside - Excellent optical properties and offers good dimensional stability for 1 & 2 side lamination

Typical Properties					
	Property		Unit	Test Method	Value
GIF Supplies 125mic Encap True Matt	Thickness		(μm)		125
	Yield		m ² /kg .	ASTM D 4321	7.9
	Unit Weight		g/m ²		128
	Haze			ASTM D1003	≥75
	Gloss		60°	ASTM D 2457	≤10
	Wetting Tension	B	Dynes/cm	ASTM D 2578	42
		A			38
	Application Temperature	A	°C		110-130
	A: Adhesive Side B: Matt Side				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.



Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
T: 01844 208308, F: 01844 208608
Email: info@gifsupplies.co.uk
www.gifsupplies.co.uk