



## TECHNICAL DATA SHEET

### THERMAL ANTISCRATCH MATT 30 MICRON

#### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Thermal lamination film with **MATT ANTISCRATCH COATING** - Both side Corona treated - Low melt adhesive coating inside - Excellent scratch resistance

Typical Properties					
GIF Supplies Thermal Antiscratch	Property		Unit	Test Method	Value
	Thickness		( μm )	ASTM E 252	30
	Yield		m <sup>2</sup> /kg .	ASTM D 4321	37,04
	Unit Weight		g/m <sup>2</sup>	DER - 009	27,0
	Haze		%	ASTM 1003	85
	Gloss 60°	B	%	ASTM D 2457	14,00
	Wetting Tension	B	Dyne	ASTM D 2578	>42
	C.O.F	B/B		ASTM D 1894	0,4
	Application Temperature	A			≥ 110
	A: Inside B: Antiscuff Side				

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
 T: 01844 208308, F: 01844 208608  
 Email: [info@gifsupplies.co.uk](mailto:info@gifsupplies.co.uk)  
[www.gifsupplies.co.uk](http://www.gifsupplies.co.uk)