



## TECHNICAL DATA SHEET

### Thermal Sandy/Gritty Matt 50 MICRON

#### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Thermal lamination film with a **SANDY/GRITTY** texture and **Matt** finish - Both side Corona treated - Low melt adhesive coating inside - Glueable, stampable & UV Varnish receptive

Typical Properties				
Property		Unit	Test Method	Value
Thickness		( μm )		50
Yield		m <sup>2</sup> /kg .	Internal Method	31.06
Gloss	B	%	ASTM D 2457 45°	9
Wetting Tension	B	Dynes/cm	ASTM D 2578	≥ 38
C.O.F Film/Film (Static)	B/B		ASTM D 1894	0,5
Maximum Roughness Profile		μ	ISO EN 4288	15-30
Application Temperature	A	°C	Internal Method	110-120
Lamination Strength		N/25.4mm	Internal Method	≥ 7,5
A: Adhesive Side B: Sandy/Gritty Coating Side				

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
 T: 01844 208308, F: 01844 208608  
 Email: info@gifsupplies.co.uk  
 www.gifsupplies.co.uk