



## TECHNICAL DATA SHEET

### THERMAL SOFT TOUCH PRESTIGE 30 MICRON

#### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) -Thermal lamination film with **SOFT TOUCH** finish - Exclusive Peach skin texture and superior bonding strength - Enhances original colours of your print - Outstanding surface adhesion of all types of coatings, inks & foils - Improved machinability compared with previous versions - Low melt adhesive inside

Typical Properties					
GIF Supplies Thermal Soft Touch Prestige	Property		Unit	Test Method	Value
	Thickness		( µm )	ASTM E 252	30
	Yield		m <sup>2</sup> /kg .	ASTM D 4321	37,5
			ln <sup>2</sup> /Lb		26,333
	Unit Weight		g/m <sup>2</sup>	Derprosa - 009	27,0
	Gloss	B	%	ASTM D 2457 45°	6
	Wetting Tension	B	Dynes/cm	ASTM D 2578	≥ 46
	C.O.F Film/Film	B/B			0.75
	Application Temperature	A	°C		105 - 120
			°F		220-250
	Lamination Strength	A	N25,4/mm		≥ 7,5
			Lb/ln		≥ 1,68
	A: Adhesive Side B: Soft Touch Side				

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

**Graphic Image Films Ltd.**  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
**T: 01844 208308, F: 01844 208608**  
**Email: info@gifsupplies.co.uk**  
**www.gifsupplies.co.uk**