



TECHNICAL DATA SHEET

THERMAL VELVET 30 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Thermal lamination film with **VELVET** finish - Smooth velvet feel with good antiscratch properties - Excellent clarity by contact - No tonality lost after lamination - Both side Corona treated - Low melt adhesive coating inside

Typical Properties				
Property		Unit	Test Method	Value
Thickness		(μm)	ASTM E 252	30
Yield		m^2/kg .	ASTM D 4321	34,72
Unit Weight		g/m^2		28.8
Gloss	B	Gardner	ASTM D 2457 45°	5-6
Wetting Tension	B	Dynes/cm	ASTM D 2578	36
	A			50
Application Temperature	A	$^{\circ}\text{C}$		100-120
A: Adhesive Side B: Velvet Side				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic **Image** Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
T: 01844 208308, **F:** 01844 208608
Email: info@gifsupplies.co.uk
 www.gifsupplies.co.uk