

TECHNICAL DATA SHEET

WET GLOSS 12 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Wet lamination film with **GLOSS** finish - Both side Corona treated - Excellent optical properties - Good Anti-static properties - Slip modified for high speed lamination

Typical Properties				
Property		Unit	Test Method	Value
Thickness		(µm)	ASTM E 252	12
Yield		m ² /kg .	ASTM D 4321	92,6
Unit Weight		g/m ²		10,8
Gloss	B		ASTM D 2457 45°	137,4
	A			138,6
Wetting Tension	B	Dynes/cm	ASTM D 2578	38
	A			38
C.O.F Film/Film (Kinetic)	B/B		ASTM D 1894	0,21
Haze		%	ASTM D 2457	1,8
Tensile Strength	MD	kg/mm ²	ASTM D 882	13,3
	TD			31,4
Elongation at Break	MD	%	ASTM D 882	171
	TD			47
Heat Shrinkage	MD	%	ASTM D 1204	4,6
	TD			1,6
A: Inside B: Outside				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
T: 01844 208308, F: 01844 208608
Email: info@gifsupplies.co.uk
www.gifsupplies.co.uk