



# TECHNICAL DATA SHEET

## Wet Sandy/Gritty Matt 50 MICRON

### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Wet lamination film with a **SANDY/GRITTY** texture and **Matt** finish - Both side Corona treated - Low melt adhesive coating inside - Glueable, stampable & UV Varnish receptive

Typical Properties						
	Property		Unit	Test Method	Value	
GIF Supplies Wet Sandy/Gritty Matt	Thickness		( μm )		38	
	Yield		m <sup>2</sup> /kg .	Internal Method	53.76	
	Gloss	B	%	ASTM D 2457 45°	12	
	Wetting Tension	B	Dynes/cm	ASTM D 2578	≥ 38	
	C.O.F Film/Film (Static)	B/B		ASTM D 1894	0,5	
	Maximum Roughness Profile		μ	ISO EN 4288	15-30	
	A: Adhesive Side    B: Sandy/Gritty Coating Side					

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.



**Graphic Image Films Ltd.**  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
**T: 01844 208308, F: 01844 208608**  
**Email: info@gifsupplies.co.uk**  
**www.gifsupplies.co.uk**