



TECHNICAL DATA SHEET

WET SOFT TOUCH MATT 17 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) Wet lamination film with **SOFT TOUCH** finish - Smooth velvet feel with good antiscratch properties and excellent clarity by contact - No tonality lost after lamination - Corona treated

Typical Properties					
Property		Unit	Test Method	Value	
Thickness		(μm)	ASTM E 252	17	
Yield		m ² /kg .	ASTM D 4321	64,6	
		ln ² /Lb		45,449	
Unit Weight		g/m ²	Derprosa - 009	15,5	
Haze		%	ASTM 1003	95	
Gloss	B	%	ASTM D 2457 60°	4	
Tensile Strength at Break	MD	N/mm ² Lb/in ²	ASTM D 882	115	16,710
	TD			235	34,146
Elongation at Break	MD	%	ASTM D 882	165	
	TD			50	
Thermal Shrinkage	MD	%	ASTM D1204 120°C, 5min	4	
	TD			1,5	
Wetting Tension	B	Dynes/cm	ASTM D 2578	>42	
	A			>37	
C.O.F Film/Film	B/B		ASTM D 1894	0.45	
A: Inside B: Soft Touch Side MD: Machine Direction TD: Transverse Direction					

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info@gifsupplies.co.uk
www.gifsupplies.co.uk